

80-Yard, Tri-Axle, Demolition Dump Trailer

General: This Specification is for a GTDD353-36-80Y, 80-Yard, Tri Axle, Demolition Dump Trailer. With a Maximum Capacity of 70,000 lbs and a Shipping Weight of 25,900 lbs +/- 3%.

Dimensions:

- Overall Length: 36'
- Overall Width: 8' 6"
- Overall Height: 144"
- Inner Width: 94"
- Front Wall Height: 78"
- Rear Wall Height: 96"
- King Pin Setting: 18"
- King Pin Height 51"



Frame:

- Main Beam: 16" I-Beam main frame.
- Longitudinals: 6" 10 gauge grade 50 steel full length.
- Floor Sills: 4" Jr. I-Beam on 12" centers.
- Side Walls: 96" & 78" High, 10 gauge grade 50 steel and 4 x 6 structural tubing with 3" x 3" angle on top.
- Floor: 1/4" grade 50 steel with 4 rows of 2" x 2" angle.

Tailgate: Heavy duty barn door type gate, hinged & lockable.

Axles: 3-ea 25,000 Lb capacity, front axle air lift.

Landing Gear: 2-speed landing gear, static load capacity 160,000 lbs, lifting capacity 50,000 lbs, side capacity 29,000 lbs.

Wheels & Tires:

- o Tires: 12-ea 255/70R x 22.5 "H" load range, steel belted radials.
- o Wheels: 12-ea. 8.25 x 22.5, 10 hole hub piloted steel disc wheels.

Brakes: 16 1/2" x 7" air brakes with automatic slack adjusters, 30/30 spring parking brake on back two axles with ABS 2S1M system & type 30 on front lift axle.

Suspension: Heavy duty single point spring ride suspension.

Electrical: 12-Volt electrical system with standard 7 way SAE connector, all lighting in rubber grommet mountings to DOT specifications.

Tarp System: Automatic tarp system, with cab kit for in cab operation.

Finish: Sandblasted to near white, primed with standard top coating, and choice of colors. (std. Black)

Options:

- Manual tarp box
- Dual gate (barn door & swing style)
- Available in tandem axle configuration.

Warranty: 3 years against defects in materials and workmanship



GLOBE TRAILER MFG., INC.

3101 59th Ave. Dr. E. - Bradenton, FL - 34203
P: (941)753-2199 F: (941)755-7604 E: sales@globetrailers.com