



60-Ton, 3 Axle, Detachable Gooseneck, Non-Ground Bearing, Lowboy Trailer

General: This Specification is for Model GTBN603-53-26-HGG, 60-Ton, 3 Axle, Detachable Gooseneck, Non-Ground Bearing, Lowboy Trailer with a Maximum Payload of 120,000 lbs in 12' Load Concentration and a Shipping Weight of 22,900 lbs +/- 3%.

Dimension:

- Overall Length: 52' 6" (630")
- Overall Width: 8' 6" (102")
- Gooseneck: 12' 4" (145")
(98" Swing Clearance & 4-Position Ride Height)
- Loadwell Length: 26' (312")
- Rear Deck: 14' 2" (170")
- Loadwell Height: 24"
(8" Ground Clearance)
- 5th Wheel Height: 50"
- King Pin Setting: 16"

Frame:

- Main Beam: 16" fabricated T-1 "I" beam, 100,000 PSI.
- Cross Member: 10" Jr. "I" beams on 12" Centers
- Side Rails: 16" fabricated T-1 "I" beam, 100,000 PSI.
- Rear Tail: 14" fabricated T-1 "I" beam, 100,000 PSI.

Axles:

3 - 25,000 lbs capacity axles, 3rd axle lift.

King Pin:

2" heavy duty, AAR rated.

Wheels & Tires:

Tires: 12 ea 275/70R x 22.5 "H" load range, steel belted radials.

Wheels: 12 ea. 8.25 x 22.5, 10 hole hub piloted steel disc wheels.

Brakes:

16.5 x 7 full air brakes with spring parking brakes, automatic slack adjusters, and 2SIM ABS system on 1st two axles.

Suspension:

Cush air ride yoke mount suspension, 3rd axle air lift, with auto dump valve, & +/- 3 air ride adjustment.

Front Ramps:

26" double hinged front loading flip ramps with grousers.

Rear Tail Section:

Open wheel with boom & bucket well, set up for 4th axle flip.

Electrical:

12-Volt electrical system with standard 7 way SAE connector, all lighting LED in rubber grommet mounted to DOT standards.

Hydraulics:

Wet line hook-up for tractor PTO operation.

Decking:

2" oak flooring, open center, secured to frame with 5/16" self-taping torque screws.

Tie Downs:

22 ea "D" Ring tie downs 9 ea side on main deck, 2 on rear deck.

Out Riggers:

32 ea removable outriggers with double up front and double in middle of loadwell, Lock-In-Lock-Out 16 ea Side.

Finish:

Sandblasted to near white primed and top coated standard color of choice.



Options:

- Additional Lengths & Widths: (20' - 30' optional lengths, 103" - 144" optional widths - permit may be required).
- Gooseneck: Additional swing clearances (80" - 120"), additional ride height (7-Position).
- Power Pack Hydraulics: 9hp-18hp gas engine or diesel, combo power pack/wet line kit available.
- Lockable toolbox & chain storage
- Spare tire & wheel: 275/70R x 22.5 "H".
- Optional tire sizes available
- Rear Deck: 1/4" diamond plate steel wheel covers.
- Decking: Rumber (no warranty), Apitong, & Pine.
- Ramps: Spring or hydraulic with beaver tail, optional lengths & widths.
- 4th axle flip w/air and electrical.

Warranty:

10 years against defects in material & workmanship.

OPERATING PRESSURE/GPM
Wet Kit System requires 3000 PSI at 10 GPM
Maximum flow to lift load at full capacity



GLOBE TRAILER MFG., INC.

3101 59th Ave. Dr. E. - Bradenton, FL - 34203
P: (941)753-2199 F: (941)755-7604 E: sales@globetrailers.com